

Ratings	20' Standard	40' Standard	40' HC Standard
Maximum Gross Weight	30,480 kg (67,200 lb.)	30,480 kg (67,200 lb.)	30,480 kg (67,200 lb.)
Tare Weight	2,200 kg (4,850 lb.)	3,655 kg (8,050 lb.)	3,870 kg (8,532 lb.)
Payload	28,280 kg (62,350 lb.)	26,825 kg (59,142 lb.)	26,610 kg (58,668 lb.)
External Dimensions			
Length	6,058 mm (19'-10½")	12,192 mm (40'-0")	12,192 mm (40'-0")
Width	2,438 mm (8'-0")	2,438 mm (8'-0")	2,438 mm (8'-0")
Height	2,591 mm (8'-6")	2,591 mm (8'-6")	2,896 mm (9'-6")
Internal Dimensions			
Length	5,900 mm (19'-4¼")	12,025 mm (39'-5½")	12,025 mm (39'-5½")
Width	2,348 mm (7'-8½")	2,348 mm (7'-8½")	2,348 mm (7'-8½")
Height	2,385 mm (7'-9 7/8")	2,385 mm (7'-9 7/8")	2,690 mm (8'-9 7/8")
Door Opening			
Width	2,340 mm (7'-8 1/8")	2,340 mm (7'-8 1/8")	2,340 mm (7'-8 1/8")
Height	2,275 mm (7'-5 5/8")	2,275 mm (7'-5 5/8")	2,578 mm (8'-5½")
Cube			
Cubic Capacity	33.04 m³ (1,166 ft.³)	67.34 m³ (2,377 ft.³)	75.95 m³ (2,681 ft.³)
Test Loads			
Stacking	97,200 kg (214,290 lb.)	97,200 kg (214,290 lb.)	97,200 kg (214,290 lb.)
Transverse Racking	15,240 kg (33,600 lb.)	15,240 kg (33,600 lb.)	15,240 kg (33,600 lb.)
Longitudinal Racking	7,620 kg (16,800 lb.)	7,620 kg (16,800 lb.)	7,620 kg (16,800 lb.)
Floor Strength	7,260 kg (16,000 lb.)	7,260 kg (16,000 lb.)	7,260 kg (16,000 lb.)